

Diese Internetseite verwendet Cookies, um die Nutzererfahrung zu verbessern und den Benutzern bestimmte Dienste und Funktionen bereitzustellen. Durch die weitere Nutzung stimmen Sie dem zu. [OKDetails](#)

Anschrift	SAFTI FIRST - Clear Fire Rated Glass & Framing A division of O'Keeffe's, Inc. 100 N Hill Dr Ste 12 94005 Brisbane
Land	USA

PRODUKTE ODER MASCHINEN

SuperLite I - Fire Protective Specialty Tempered

20 minute, CPSC Cat. II, clear specialty tempered glazing. Decorative options also available.

SuperLite I-XL - Fire Protective Specialty Tempered with Partial Radiant Heat Protection

20-45 minute, CPSC Cat. II, directional clear specialty tempered glazing with partial radiant heat protection.

SuperLite I-XL IGU - Fire Protective Specialty Tempered with Partial Radiant Heat Protection

20-45 minute, CPSC Cat. II, bi-directional clear specialty tempered glazing with partial radiant heat protection.

SuperLite I-W - Fire Protective Wired with Safety Film

20-90 minute, CPSC Cat. II safety wired glazing.

SuperLite X-45/60/90 - Fire Protective Door Lites up to 100 sq. in.

45-90 minute clear, non-wired, and tint free glazing that meets all the fire and safety requirements for doors up to 100 square inches.

SuperLite II-XL 45 - Fire Resistive Tempered Glazing

45 minute, CPSC Cat. II, ASTM E119 tested, clear transparent glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance, and unlimited decorative options.

SuperLite II-XL 60 - Fire Resistive Tempered Glazing

60 minute, CPSC Cat. II, ASTM E119 tested, clear transparent wall glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance, and unlimited decorative options.

SuperLite II-XL 90 - Fire Resistive Tempered Glazing

90 minute, CPSC Cat. II, ASTM E119 tested, clear transparent wall glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance, and unlimited decorative options.

SuperLite II-XL 120 - Fire Resistive Tempered Glazing

120 minute, CPSC Cat. II, ASTM E119 tested, clear transparent wall glazing that blocks radiant heat transfer. Can be customized to include energy performance, noise abatement benefits, bullet resistance, hurricane resistance, and unlimited decorative options.

SuperLite II-XLB - Fire Resistive Tempered Glazing for Oversized and Butt-Glazed Applications

60-120 minute, CPSC Cat. II, ASTM E-119 tested, fire resistive tempered glazing that blocks radiant heat transfer. Butt-glazed assemblies and other decorative glass make-ups available.

SuperLite II-XLM 45 - Fire Resistive Multilaminate Glazing

45 minute, CPSC Cat. II, ASTM E119 tested, clear fire resistive multilaminate glazing that blocks radiant heat transfer. Can be customized to include energy-saving insulated units, decorative, security and more.

SuperLite II-XLM 60 - Fire Resistive Multilaminate Glazing

60 minute, CPSC Cat. II, ASTM E119 tested, clear fire resistive multilaminate glazing that blocks radiant heat transfer. Can be customized to include energy saving insulated units, decorative, security and more.

SuperLite II-XLM 90 - Fire Resistive Multilaminate Glazing

90 minute, CPSC Cat. II, ASTM E119 tested, clear fire resistive multilaminate glazing that blocks radiant heat transfer. Can be customized to include energy saving insulated units, decorative, security and more.

SuperLite II-XLM 120 - Fire Resistive Multilaminate Glazing

120 minute, CPSC Cat. II, ASTM E119 tested, clear fire resistive multilaminate glazing that blocks radiant heat transfer. Can be customized to include energy-saving insulated units, decorative, security and more.

Super Secure II-XLS 45-120 - Fire Resistive Security Glazing

45-120 minute, CPSC Cat. II, ASTM E119 tested, clear transparent wall glazing that blocks radiant heat transfer and meets forced entry requirements.

Pyran Platinum - Fire Protective Non-safety Ceramic

20-90 minute, environmentally friendly ceramic glass free from tints and noticeable distortions without the added cost of polishing. No impact resistance.

Pyran Platinum F - Fire Protective Filmed Safety Ceramic

20-180 minute, environmentally friendly, filmed ceramic glass free from tints and noticeable distortions without the added cost of polishing. Impact safety rated to CPSC Cat. II.

Pyran Platinum L - Fire Protective Laminated Safety Ceramic

20-180 minute, environmentally friendly, laminated ceramic glass free from tints and noticeable distortions without the added cost of polishing. Impact safety rated to CPSC Cat. II.

GPX Architectural Series

Fire protective and resistive, aluminum framing system available in multiple profiles. Offered in standard and custom finishes, including powder coat, clear anodized, bronze anodized, black anodized, Kynar® 500 coatings, Valspar®, Decoral®, any species of wood veneer, ornamental metal, and many more. Optional make-up meets Level 8 ballistic rating, per UL 752-2005.

GPX Builders Series Fire Protective

Fire protective framing system available in multiple profiles. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, black anodized, Decoral®, any species of wood veneer, ornamental metal, and more.

GPX Builders Series Temperature Rise

Temperature-rise door framing system available in multiple custom profiles. Offered in standard and custom finishes including high performance fluoropolymer finishes by PPG, clear anodized, bronze anodized, black anodized, Decoral®, any species of wood veneer, ornamental metal, and more.

GPX Curtain Wall System

Fire resistive aluminum framing system available in multiple profiles for multi-story spans of glass.

GPX Hurricane System

Fire resistive, hurricane rated, aluminum framing system. Offered in standard and custom finishes, including powder coat, clear anodized, bronze anodized, black anodized, Kynar® 500 coatings, Valspar®, Decoral®, any species of wood veneer, ornamental metal, and many more.

GPX Hurricane System with Florida Product Approval

Fire resistive, hurricane rated, aluminum framing system. Offered in standard and custom finishes, including powder coat, clear anodized, bronze anodized, black anodized, Kynar® 500 coatings, Valspar®, Decoral®, any species of wood veneer, ornamental metal, and many more.

GPX Ballistic System

Fire resistive, ballistic rated aluminum framing system available in multiple profiles. Offered in standard and custom finishes, including powder coat, clear anodized, bronze anodized, black anodized, Kynar® 500 coatings, Valspar®, Decoral®, any species of wood veneer, ornamental metal, and many more.

GPX Blast System

Fire resistive, blast rated aluminum framing system available in multiple profiles. Offered in standard and custom finishes, including powder coat, clear anodized, bronze anodized, black anodized, Kynar® 500 coatings, Valspar®, Decoral®, any species of wood veneer, ornamental metal, and many more.

GPX FireFloor System

Fire resistive restrained glass floor assembly that allows daylight to penetrate further into the building while meeting fire rated requirements.

Company Profile of **SAFTI FIRST - Clear Fire Rated Glass & Framing**

A service of glasssglobal.com, an affiliate of glasssglobal group.

Die auf dieser Seite ausgedruckten Firmeninformationen unterliegen dem Urheberrecht und sind Eigentum der entsprechenden Firma. Alle Rechte sind ausdrücklich vorbehalten. Jeder Nutzer, der sich Zugang zu diesem Material zugänglich macht, tut dies zu seinem persönlichen Gebrauch und die Nutzung dieses Materials unterliegt seinem alleinigen Risiko. Die Weiterverteilung und jegliche andere gewerbliche Verwertung des vorliegenden Adressenmaterials ist ausdrücklich untersagt. In den Fällen, in denen solches Adressenmaterial durch eine dritte Partei beigestellt wurde, erklärt jeder Besucher sein Einverständnis, die speziellen zutreffenden Nutzungsbedingungen anzuerkennen und sie zu respektieren. Glass Global garantiert oder bürgt nicht für die Genauigkeit oder die Zuverlässigkeit von irgendwelchen Informationen, die in den veröffentlichten Adressinformationen enthalten sind, oder auch in Webseiten auf die hier Bezug genommen wird. www.glasssglobal.com - Die Internationale Portalseite für die Glasindustrie - OGIS GmbH