

Diese Internetseite verwendet Cookies, um die Nutzererfahrung zu verbessern und den Benutzern bestimmte Dienste und Funktionen bereitzustellen. Durch die weitere Nutzung stimmen Sie dem zu. [OKDetails](#)

Anschrift	Sphere Hotwork 36/FF, Maruti Complex, Opp. 390002 Vadodara
Land	Indien

PRODUKTE ODER MASCHINEN REFRACTORY DRYOUT

It is very much important that proper dryout of refractories should be undertaken as water is the common solvent for mixing of mortars, rams, castables , cements used for installation. This water which is hydraulically bonded through chemical interactions, between various refractories after installation needs to be driven out from the lining or else can cause a severe crack by trapping steam in the lining which shall ultimately give way to the entire castable lining. To ensure optimum refractory performance it is imperative that all moisture is removed thoroughly and uniformly during the course of heat-up and prior to the plant being subjected to onstream production.

General description of the procedure of the dry-out of a refractory lining:

For the dry-out of a refractory lining external High velocity burners are used. These external burners are fired with light weight oil/Gas and will be installed in openings like manholes or doors.

One burner unit exists of the mobile burner with the Extended Nozzle, the Combustion fan, regulation flap for the combustion air, the connecting air duct and the regulation unit. The fans are sucking the ambient air and compress it up to max. 60 mbar. This air used for combustion of the burner.

The burner itself consists of the combustion chamber in which the fuel oil and compressed air/Gas will be mixed with the combustion air and ignited and the steel part (extended nozzle, manufactured of heat resistant steel) which will lead the flue gases. These extended nozzle could be straight or with an angle and the end so that the flue gas could be led to a desired direction and critical parts close to the burner will not be "touched" directly by the flue gases.

The air duct is used for the compressed ambient air to the burner.. The required temperature of the outgoing flue gases will be controlled and achieved by controlling fuel oil by our specialists who are on site continuously.

The flue gas temperature is controlled manually by controlling oil flow by valve of the oil train to achieve required temperature as per the heating schedule.

The maximum temperature reading of all the thermocouple placed in equipment will be considered as target temperature.

Cement Industry

PreHeater & Cyclones
Rotary Kilns & Inter Coolers
C coolers
Rawmills
Cement Mills

Power Industry

C.F.B.C. Boilers
Seal Port
ASH Cooler & Cyclones
Waste Heat Boilers

Combustions Beds
Ducts
Coal Collector
Kiln

Steel Industry

Hot Blast stove / Furnace
Metallic Pre-Heater reactor
Runners & Laddles
Blast Furnace Dryout
Hot Blast main
Bustle Pipe Dryout
Cokeovens

Aluminium Industry

Furnace
Cyclones
Rotary Linns & Inter Coolers
Calciner

Copper Industry

Copper Smelters
Anode Furnaces & Laddlers
Chimney's

Fertilizer & Chemical Industry

Lime Kiln
Secondary Reformer
R.G. Boilers
Reactor
Heat Exchanger & Reformer
Incinerator

Petro Chemicals

Sulphur Furnace
FCCU / SRU / BBU
Reactor
Sulphur Condenser
Main Combustion Chambers / Fired Heaters / Stacks
Primary Reformer
Secondary Reformer
Vacun Heaters
Incinerator

Non Ferrous metal

Aluminium Holding Furnaces
Aluminium Melting Furnaces
Induction Furnaces
Tilting Furnaces

Company Profile of **Sphere Hotwork**

A service of glassglobal.com, an affiliate of glassglobal group.

Die auf dieser Seite ausgedruckten Firmeninformationen unterliegen dem Urheberrecht und sind Eigentum der entsprechenden Firma. Alle Rechte sind ausdrücklich vorbehalten. Jeder Nutzer, der sich Zugang zu diesem Material zugänglich macht, tut dies zu seinem persönlichen Gebrauch und die Nutzung dieses Materials unterliegt seinem alleinigen Risiko. Die Weiterverteilung und jegliche andere gewerbliche Verwertung des vorliegenden Adressenmaterials ist ausdrücklich untersagt. In den Fällen, in denen solches Adressenmaterial durch eine dritte Partei beigestellt wurde, erklärt jeder Besucher sein Einverständnis, die speziellen zutreffenden Nutzungsbedingungen

anzuerkennen und sie zu respektieren. Glass Global garantiert oder bürgt nicht für die Genauigkeit oder die Zuverlässigkeit von irgendwelchen Informationen, die in den veröffentlichten Adressinformationen enthalten sind, oder auch in Webseiten auf die hier Bezug genommen wird. www.glassglobal.com - Die Internationale Portalseite für die Glasindustrie - OGIS GmbH